



Addressable

# POE Enabled Multisensor

Model : PTSPEMSX501

## Datasheet

<http://www.pinetreesystems.com>



### Outline

IP based Multisensor is a POE Powered Photoelectric device with built-in POE & Network protocol that utilizes Network for establishing reliable Communication. The detector is intended to be used with PineTree's Network IP Based Fire Alarm Control Panel and other compatible devices. These detectors are tagged with a unique electronic ID which helps to speed up the response time of emergency personnel by pin-pointing the location of the alarm source. POE devices are also housed with optional Wifi connectivity to provide easy expansion and connectivity.

### Features

- POE Enabled
- Low standby current
- Built in Access Point
- Sleek, low-profile design
- Removable cover and insect screen

### Technical Specification

<b>Product Class</b>	: IP - POE - Addressable
<b>Sensor</b>	: Photoelectric + Heat
<b>Power Supply</b>	: POE / 9V Battery(optional)
<b>Housing</b>	: ABS
<b>Alarm Output</b>	: RED LED
<b>Operating Temperature</b>	: -10°C to +55°C
<b>Operating Humidity</b>	: <95% Non Condensed
<b>Addressing Method</b>	: Electronic
<b>Connectivity</b>	: RJ45 / WiFi

### Compliance

CE-5336  
Complied with  
EN54-7

